

Sicherheitsschrank Typ 90 - EN 14470-1 - Untertisch 1 Tür - Verwertung von Abfallstoffen

ÜBEREINSTIMMUNG

ADVANTAGES

- EN 14470-1 Type 90 compliant
- Storage of flammables

SONDERN AUCH...

- Thermo-expanding seals of the doors
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory
- Complete system for recovery of waste provided



TECHNISCHE DATEN

| | | | |
|-----------------------------------|----------------------|--------------------------------|---|
| Referenz | 791+ARD | Verriegelung der Türen | selbstschließend |
| Baustoffe der Sicherheitsschränke | Stahl 12/10 | Versandabmessungen HxBxT (mm) | 900 x 1200 x 800 |
| Türfarbe | weiß RAL 9010 | Belüftung | zuluftöffnung und abluftöffnung an der Rückseite |
| Anzahl der Türen | 1 | Durchmesser der Öffnungen (mm) | 100 |
| Art der Türen | flügeltüren | Anzahl der Abteile / Fächer | 1 |
| Scharniere | rechts | Codenummer | 94032080 |

COMPLEMENTARY ACCESSORIES - VENTILATION AND FILTRATION BOXES

- Filteraufsätze mit filter für organische Dämpfe (Réf : CDF-A)
- Lüftungskasten (Réf : CDV-A)
- Anschlüsse für Filteraufsätze (Réf : KRC)
- Filteraufsätze (ohne Filter) - NF X 15-211 (Réf : H40+)

| Referenz | Außere Abmessungen HxBxT (mm) | Innere Abmessungen HxBxT (mm) | Lagerkapazität (L) | Auffangwanne | Regale | Tragfähigkeit | Gewicht (Kg) |
|----------|-------------------------------|-------------------------------|--------------------|--------------|--------|---------------|--------------|
| 791+ARD | 630 x 635 x 570 | 420 x 490 x 285 | 30 | | 0 | 0 | 160.00 |