

7031T



1- sliding door underbench safety cabinet Type 30

COMPLIANCE

EN 14470-1

ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables, corrosives and toxics

BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable leveling feet for enhance stability
- Tested and approved according to FM 6050
- Normalized labelling provided with the equipment
- Locking system
- Holes for the connection to the ventilation



TECHNICAL FEATURES

Model	7031T	Door closure	manual closing
Compliance	EN 14470-1	Shipping dimensions HxWxD (mm)	835 x 1200 x 800
Cabinet materials	Melamine wood structure	Ventilation	Both inlet and outlet on the back wall of the cabinet
Doors color	light grey RAL 7035	Openings diameter (mm)	100
Number of doors	1	Number of compartments	1
Doors type	sliding doors	HS Code	94036000

ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

OPTIONS

- Perforated cover plate for cabinets 761T - 791T (Réf : C1T)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
7031T	635 x 605 x 630	310 x 495 x 475	30		0	30	64.00