

# 1- sliding door underbench safety cabinet Type 60

## COMPLIANCE

EN 14470-1, EN 1363-1

## ADVANTAGES

- 60-minute fire resistant and made in France
- EN 14470-1 and EN 1363-1 compliant
- Storage of flammables

## BUT ALSO...

- Thermo-expanding seals of the doors
- EN 14470-1 Type 60 compliant
- Adjustable shelves in height
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- Tested and approved with ISO 834 fire heating curve by an European laboratory



## TECHNICAL FEATURES

|                   |                                              |                                |                                                              |
|-------------------|----------------------------------------------|--------------------------------|--------------------------------------------------------------|
| Model             | <b>762T</b>                                  | Door closure                   | <b>manual closing</b>                                        |
| Compliance        | <b>EN 14470-1, EN 1363-1</b>                 | Shipping dimensions HxWxD (mm) | <b>900 x 1200 x 800</b>                                      |
| Cabinet materials | <b>12/10th epoxy painted steel structure</b> | Ventilation                    | <b>Both inlet and outlet on the back wall of the cabinet</b> |
| Doors color       | <b>white RAL 9010</b>                        | Openings diameter (mm)         | <b>100</b>                                                   |
| Number of doors   | <b>1</b>                                     | Number of compartments         | <b>1</b>                                                     |
| Doors type        | <b>sliding doors</b>                         | Containment sump               | <b>1</b>                                                     |
| Hinges            | <b>right &amp; left</b>                      | HS Code                        | <b>94032080</b>                                              |

## ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

## OPTIONS

- Perforated cover plate for cabinets 762T - 792T (Réf : C2T)

| Model | External dimensions HxWxD (mm) | Internal dimensions HxWxD (mm) | Storage capacity (L) | Containment sump | Shelves | Load capacity | Weight (kg) |
|-------|--------------------------------|--------------------------------|----------------------|------------------|---------|---------------|-------------|
| 762T  | 670 x 1135 x 615               | 460 x 1000 x 380               | 60                   | 1                | 0       | 0             | 240.00      |