

7635BG



2- door tall safety cabinet Type 30 for gas cylinders

COMPLIANCE

EN 14470-2, EN 1363-1

ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-2 and EN 1363-1 compliant

BUT ALSO...

- Tested and approved Type 30 according to EN 14470-2 and EN 1363-1
- Normalized labelling provided with the equipment
- Pedestal area under-driveable by a forklift by removing panel
- Double wall construction
- Locking system
- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Adjustable leveling feet for enhance stability
- 30-minute fire resistance
- Tested and approved by a independent European laboratory



TECHNICAL FEATURES

Model	7635BG	Hinges	right
Compliance	EN 14470-2, EN 1363-1	Door closure	manual closing
Cabinet materials	Built in double wall melamine (thickness: 76mm) :	Ventilation	outlet located at the bottom of the cabinet, inlet located at the top
Doors color	Grey structure (RAL 7035), yellow edges (RAL 1023)	Openings diameter (mm)	100
Number of doors	1	HS Code	94032080
Doors type	swing doors		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Horizontal rail for mounting 4 cylinders B50 (Réf : RH5BG)
- Galvanized steel ramp for 7634BG or 7635BG (Réf : RABG)

OPTIONS

- Shelf for 1 cylinder type B2, B5, B10, B11, B15 or B20 (Réf : EG1)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
7635BG	2055 x 1200 x 665	1753 x 1048 x 458	4		0	0	447.00