G804+LI10




# Storage and display cabinet – counter, 2-door – P1000T1

## COMPLIANCE

## ADVANTAGES

- Connected alarm | smoke detector
- Open-door alarm
- Circuit breaker
- Fire extinguisher
- Flame protection system
- Ballistic protection system
- Manual security check
- Dry contact
- Storage of lithium-ion batteries
- French manufacturing - CSR

### BUT ALSO...

- Locking system
- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Reduce the risk of fire and explosion

## TECHNICAL FEATURES

| | | | |
|---|---|---|---|
| Model | **G804+LI10** | Ventilation | **Both inlet and outlet on the top of the cabinet** |
| Cabinet materials | **12/12 double-walled steel** | Openings diameter (mm) | **100** |
| Doors color | **white RAL 9010** | Connecting sleeve | **1** |
| Number of doors | **2** | Number of compartments | **1** |
| Doors type | **swing doors** | HS Code | **94032080** |
| Hinges | **left and right** | | |

## ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Rack of 9 electrical outlets (Réf : PRISELI)
- Rack of 6 electrical outlets equipped with a thermal-magnetic circuit breaker (Réf : PRISELICC)
- Rack of 7 G-type electrical outlets (UK) (Réf : PRISELIUK)
- Rack of 8 electrical outlets type J (Switzerland) (Réf : PRISELICH)
- Rack of 8 electric outlets type F (Germany) (Réf : PRISELIF)

| Model | External dimensions HxWxD (mm) | Internal dimensions HxWxD (mm) | Storage capacity (L) | Containment sump | Shelves | Load capacity | Weight (kg) |
|---|---|---|---|---|---|---|---|
| G804+LI10 | 935 x 1000 x 450 | 745 x 950 x 400 | 0 | | 2 | 0 | 77.00 |

TRIONYX
1er FABRICANT FRANCAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr