

H122Z+2C



Ductless fume hood 1200 mm - 2 Modules - for liquid - one opening

COMPLIANCE

ADVANTAGES

- CE certified
- NF X 15-211 compliant
- Storage of flammables, corrosives and toxics

BUT ALSO...

- Easy replacement of the active coal filter
- Low acoustic level
- Front control window to see immediately the filter
- NF X 15-211 compliant
- Delivered ready to use
- Lighting control allowing to survey the proper working of the fan
- Holes for the cables and fluid going through
- Glass side walls
- Ergonomic hand traps or trapezoidal opening



TECHNICAL FEATURES

Model	H122Z+2C	Hour counter	included
Airflow (m/s)	0,4 - 0,6	Sampling outlet	included
Voltage (volts)	220-240	Backwall transparent	included
Flow (m3/h)	170	Melamine work-top	Option
Openings for passages of cables	4	Electrical power (W)	27
Anemometer	included	Sound power of the fan dB(A)	57.00
Guide of chemicals adsorbed	included	HS Code	84146000

COMPLEMENTARY PRODUCTS

- Activated carbon filter for ammonia vapors - for old fume hoods type 200, 201, 210 and 211 (Réf : AMM200)
- Activated carbon filter for organic and corrosive vapors - for old fume hoods type 200, 201, 210 and 211 (Réf : CORG201)
- Activated carbon filter for formaldehyde vapors - for old fume hoods type 200, 201, 210 and 211 (Réf : FOR200)
- Activated carbon filter for organic vapors for H200 - H201 - H210 - H211 (Réf : ORG200)
- Activated carbon filter for organic vapors for H200 - H201 - H210 - H211 (Réf : ORG200)
- Containment sump and melamine work-top for H12 (Réf : BB12)
- Containment sump and tempered glass work-top for H12 (Réf : BV12)

OPTIONS

- Lighting for ductless fume hoods (Réf : LUMI)
- Table-cabinet for H12 (Réf : TA12)
- Trolley with adjustable shelf for H12 (Réf : TR12)
- Tubular table with feet for model H12 (Réf : TTF12)
- Tubular table with wheels for model H12 (Réf : TTR12)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Weight (kg)
H122Z+2C	1160 x 1200 x 750	935 x 1145 x 700	44.00