

MB12



1- door working cover safety cabinet for flammables

COMPLIANCE

FM - OSHA - NFPA

ADVANTAGES

- NFPA and OSHA compliant
- FM compliant
- Storage of flammables

BUT ALSO...

- Continuous piano hinges
- Containment sump at the bottom
- NFPA, OSHA and FM compliant
- Rugged construction with double wall
- Adjustable shelves in height
- Holes for the connection to the ventilation
- Integrated door handle
- Fixation for earthing



TECHNICAL FEATURES

Model	MB12	Door closure	manual closing
Compliance	FM - OSHA - NFPA	Shipping dimensions HxWxD (mm)	1160 x 600 x 800
Cabinet materials	Double wall steel structure	Ventilation	Both inlet and outlet
Doors color	yellow	Openings diameter (mm)	50
Number of doors	1	Number of compartments	1
Doors type	swing doors	Containment sump	1
Hinges	right	HS Code	2147483647

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Shelf for cabinets MB12 - SB12 (Réf : ES12)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
MB12	889 x 591 x 457	775 x 508 x 370	45	1	1	159	47.00



TRIONYX
1^{er} FABRICANT FRANÇAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr