

S2004T



2- door tall safety cabinet

COMPLIANCE

NF EN ISO 1182

ADVANTAGES

- 2- point locking system
- NF EN ISO 1182 compliant
- Storage of flammables and toxics

BUT ALSO...

- Containment sump at the bottom
- 2- point locking system
- Self-closing doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Non-flammable insulation between the walls



TECHNICAL FEATURES

Model	S2004T	Door closure	automatic closing
Compliance	NF EN ISO 1182	Shipping dimensions HxWxD (mm)	2300 x 1200 x 800
Cabinet materials	12/10th epoxy painted steel structure	Ventilation	Both inlet and outlet
Doors color	white RAL 9010	Openings diameter (mm)	100
Number of doors	2	Number of compartments	1
Doors type	swing doors	Containment sump	1
Hinges	right & left	HS Code	94032080

ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Containment sump in PVC (Réf : BP04)
- Shelf protection in PVC (Réf : EP04)
- Additional retention shelf (Réf : G04)
- Additional containment sump (Réf : GL04)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
S2004T	2095 x 1000 x 450	1945 x 950 x 400	250	1	5	75	152.00



TRIONYX
1^{er} FABRICANT FRANÇAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr