

S804T



2- door working cover safety cabinet

COMPLIANCE

NF EN ISO 1182

ADVANTAGES

- 2- point locking system
- NF EN ISO 1182 compliant
- Storage of flammables and toxics

BUT ALSO...

- Containment sump at the bottom
- 2- point locking system
- Self-closing doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Non-flammable insulation between the walls



TECHNICAL FEATURES

Model	S804T	Containment sump	1
Compliance	NF EN ISO 1182	Airflow (m/s)	0,5
Cabinet materials	12/10th epoxy painted steel structure	Voltage (volts)	220-240
Doors color	white RAL 9010	Flow (m3/h)	170
Number of doors	2	Anemometer	Oui
Doors type	Type de porte(s)	Guide of chemicals adsorbed	Oui
Hinges	right & left	Hour counter	Oui
Door closure	manual closing	Sampling outlet	Oui
Ventilation	Both inlet and outlet	Backwall transparent	Non
Openings diameter (mm)	100	HS Code	94032080
Number of compartments	1		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Containment sump in PVC (Réf : BP04)
- Shelf protection in PVC (Réf : EP04)
- Additional retention shelf (Réf : G04)
- Additional containment sump (Réf : GL04)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
S804T	895 x 1000 x 450	745 x 950 x 400	100	1	1	75	75.00



TRIONYX
1^{er} FABRICANT FRANÇAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr