

2- door underbench safety cabinet for acids and toxics

COMPLIANCE

ADVANTAGES

- Complies with risk prevention and safety recommendations
- Designed to be placed under-bench
- Storage of flammables, corrosives and toxics

BUT ALSO...

- Possibility of connection between models
- Especially designed to settle under the bench
- Equipment allowing space saving
- Locking system



TECHNICAL FEATURES

Model	AT60	Shipping dimensions HxWxD (mm)	870 x 1200 x 800
Cabinet materials	15/10th epoxy painted steel structure	Ventilation	Both inlet and outlet
Doors color	blue RAL 5015 & white RAL 9011	Openings diameter (mm)	100
Number of doors	2	Number of compartments	2
Doors type	swing doors	Containment sump	2
Hinges	right & left	HS Code	94032080
Door closure	self-closing		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Filtration box built in PVC with activated carbon filter for organic and corrosive vapors (Réf : CDF-P)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
AT60	670 x 1100 x 500	(2x) 650 x 530 x 470	60	2	2	50	60.00