

2- door underbench safety cabinet for flammables and toxics

COMPLIANCE

ADVANTAGES

- Complies with risk prevention and safety recommendations
- Designed to be placed under-bench
- Storage of flammables, corrosives and toxics

BUT ALSO...

- Especially designed to settle under the bench
- Equipment allowing space saving
- Complies with risk prevention and safety recommendations
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Doors with key locking system
- Possibility to add swivel castors, for an easy movement of the cabinet



TECHNICAL FEATURES

| | | | |
|-------------------|--|--------------------------------|------------------------------|
| Model | ST60 | Shipping dimensions HxWxD (mm) | 870 x 1200 x 800 |
| Cabinet materials | 15/10th epoxy painted steel structure | Ventilation | Both inlet and outlet |
| Doors color | yellow RAL 1023 & white RAL 9011 | Openings diameter (mm) | 100 |
| Number of doors | 2 | Number of compartments | 2 |
| Doors type | swing doors | Containment sump | 2 |
| Hinges | left | HS Code | 94032080 |
| Door closure | self-closing | | |

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

OPTIONS

- 4 swivel castors 2 with locking (Réf : 4ROU)

| Model | External dimensions HxWxD (mm) | Internal dimensions HxWxD (mm) | Storage capacity (L) | Containment sump | Shelves | Load capacity | Weight (kg) |
|-------|--------------------------------|--------------------------------|----------------------|------------------|---------|---------------|-------------|
| ST60 | 670 x 1100 x 500 | (2x) 650 x 530 x 470 | 60 | 2 | 2 | 50 | 60.00 |