

# Combination shower eyewasher for indoor use

## COMPLIANCE

EN 15154-1, EN 15154-2, NF X 15-221

## ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and EN 15154-2 compliant
- First-aid in case of chemical projection

### BUT ALSO...

- EN 15154-1 and EN 15154-2 compliant
- Allows to rinse itself the body in case of chemical projection
- Delivered with the first-aid labelling
- Anti-dust caps for dusty environment
- Compliant to the article R. 4224-14 of the Labour Code



## TECHNICAL FEATURES

|                                |  |              |                        |
|--------------------------------|--|--------------|------------------------|
| Model                          | <b>DLP62</b>                               | Bowl         | <b>stainless steel</b> |
| Compliance                     | <b>EN 15154-1, EN 15154-2, NF X 15-221</b> | Shower head  | <b>stainless steel</b> |
| Shipping dimensions HxWxD (mm) | <b>350 x 250 x 860</b>                     | Pipe         | <b>stainless steel</b> |
| Use                            | <b>internal use</b>                        | Water inlet  | <b>F1"</b>             |
| Setting                        | <b>handle and foot operating</b>           | Water outlet | <b>F1 1 / 4"</b>       |
|                                | <b>mounted on feet</b>                     | HS Code      | <b>73242921</b>        |

## OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf : MTD)

| Model | External dimensions HxWxD (mm) | Internal dimensions HxWxD (mm) | Eye-washer flow (L/min) | Shower flow (L/min) | Weight (kg) |
|-------|--------------------------------|--------------------------------|-------------------------|---------------------|-------------|
| DLP62 | 2200 x 640                     |                                | 11                      | 75                  | 22.00       |