

Combination shower eyewasher for indoor use

COMPLIANCE

EN 15154-1, EN 15154-2, NF X 15-221

ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and EN 15154-2 compliant
- First-aid in case of chemical projection

BUT ALSO...

- EN 15154-1 and EN 15154-2 compliant
- Allows to rinse itself the body in case of chemical projection
- Delivered with the first-aid labelling
- Anti-dust caps for dusty environment
- Compliant to the article R. 4224-14 of the Labour Code



TECHNICAL FEATURES

Model	DLP63	Bowl	Green ABS RAL 6029
Compliance	EN 15154-1, EN 15154-2, NF X 15-221	Shower head	Green ABS RAL 6029
Shipping dimensions HxWxD (mm)	350 x 250 x 860	Pipe	galvanised steel + green epoxy painted RAL 6029
Use	internal use	Water inlet	F1"
Setting	handle and foot operating mounted on feet	Water outlet	F1 1 / 4"
		HS Code	73242921

OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf : MTD)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
DLP63	2200 x 640		11	75	23.00

