

Combination shower eyewasher for indoor use

COMPLIANCE


EN 15154-1, EN 15154-2, NF X 15-221

ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and EN 15154-2 compliant
- First-aid in case of chemical projection

BUT ALSO...

- EN 15154-1 and EN 15154-2 compliant
- Anti-dust caps for dusty environment
- Compliant to the article R. 4224-14 of the Labour Code
- Delivered with the first-aid labelling
- Allows to rinse itself the body in case of chemical projection



TECHNICAL FEATURES

| | | | |
|--------------------------------|--|--------------|------------------|
| Model | DLV52 | Bowl | stainless steel |
| Compliance | EN 15154-1, EN 15154-2, NF X 15-221 | Shower head | stainless steel |
| Shipping dimensions HxWxD (mm) | 350 x 260 x 860 | Pipe | stainless steel |
| Use | internal use | Water inlet | F1" |
| Setting | handle and foot operating mounted on feet | Water outlet | F1 1 / 4" |
| | | HS Code | 73242921 |

OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf: MTD)

| Model | External dimensions HxWxD (mm) | Internal dimensions HxWxD (mm) | Eye-washer flow (L/min) | Shower flow (L/min) | Weight (kg) |
|-------|--------------------------------|--------------------------------|-------------------------|---------------------|-------------|
| DLV52 | 2200 x 640 | | 11 | 75 | 19.00 |