

DLP64



Combination shower eyewasher for outdoor/indoor use

COMPLIANCE

EN 15154-1, EN 15154-2, NF X 15-221

ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and EN 15154-2 compliant
- First-aid in case of chemical projection

BUT ALSO...

- EN 15154-1 and EN 15154-2 compliant
- Allows to rinse itself the body in case of chemical projection
- Delivered with the first-aid labelling
- Anti-dust caps for dusty environment
- Compliant to the article R. 4224-14 of the Labour Code



TECHNICAL FEATURES

Model	DLP64	Bowl	stainless steel + epoxy painted RAL 6032
Compliance	EN 15154-1, EN 15154-2, NF X 15-221	Shower head	Green ABS RAL 6032
Shipping dimensions HxWxD (mm)	340 x 330 x 720	Pipe	galvanised steel + grey epoxy painted RAL 7040
Use	internal use & external use handle and foot operating	Water inlet	F1"
Setting	mounted on feet	Water outlet	F1 1 / 4"
		HS Code	73242921

COMPLEMENTARY PRODUCTS

- Heating cable kit (Réf : KITCC2)

OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf : MTD)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
DLP64	2115 x 850		11	90	14.00



TRIONYX
1^{er} FABRICANT FRANÇAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr