

DS32

ISO
3864EN NFX
15154-1 15-221

Doccia di sicurezza su colonna 100% Acciai inossidabili

CONFORMIDAD

EN 15154-1, NF X 15-221

ADVANTAGES

- ISO 3864 compliant
- First-aid in case of chemical projection

SINO TAMBIÉN...

- EN 15154-1 compliant
- Delivered with the first-aid labelling
- Compliant to the article R. 4224-14 of the Labour Code



CARACTERISTICAS TECNICAS

| | | | |
|-------------|--------------------------------|---------------------|-----------------------------|
| Modelo | DS32 | Cabezal de la ducha | acciaio inossidabile |
| Conformidad | EN 15154-1, NF X 15-221 | Tubería | acciaio inossidabile |
| Uso | uso interno | Suministro de agua | F 1" |
| Fijación | comando manuale | Código Aduanero | 73242921 |
| | fissazione al suolo | | |

OPTIONS

- Mitigeur Thermostatic per doccia (Réf: MTD)

| Modelo | Dimensiones exteriores alt x anc x pro (mm) | Dimensiones interiores alt x anc x pro (mm) | Caudal de lavajos (L/min) | Caudal de la ducha de seguridad (L/min) | Peso (kg) |
|--------|---|---|---------------------------|---|-----------|
| DS32 | | | 0 | 75 | 15.00 |