

# Class II Microbiological safety cabinet, 1200 mm wide

## CONFORMITÀ

EN 12469

## ADVANTAGES

- Convenient for micro-organisms
- Low noise fan
- High intensity of light
- White walls for a glare-free brightness
- Smooth walls, rounded corners and no welds ; allowing easy cleaning and decontamination
- Easy replacement of the filters
- Ergonomic armrest for long periods of handling
- Electronic compartment located outside the contaminated area
- Alarms for : power failure, control system failure, open window, low and high airflow velocity, filters clogged

### MA ANCHE...



## CARATTERISTICHE TECNICHE

Modello	<b>PSM12</b>	Voltaggio (volt)	<b>220</b>
Conformità	<b>EN 12469</b>	Voltaggio (volt)	<b>0.99999</b>
Dimensioni di spedizione HxWxD (mm)	<b>1540 x 1450 x 850</b>	Potenza elettrica (W)	<b>1860</b>
Flusso d'aria (m/s)	<b>0,4</b>	Codice HS	<b>84146011</b>

## PRODUITS COMPLÉMENTAIRES

- Front enclosure with UV light for PSM12 (Réf : FACPSM12)
- Support stand for FLV12 and PSM12 (Réf : TH12)
- Gas valve with solenoid valve (Réf : VANGAZ)
- Vacuum valve (Réf : VANVID)

Modello	Dimensioni esterne HxWxD (mm)	Dimensioni interne HxWxD (mm)	Peso (kg)
PSM12	1400 x 1360 x 795	650 x 1190 x 600	220.00